



V-AMP: VA-2750H

POWER AMPLIFIER CLASS H

DESCRIPTIONS

The VA-2750H power amplifier class H from VL Audio. 2-channel 2,750 Watt. Durable, strong, light weight Used for touring events, concerts or installations.

FEATURE

- Temperature Protection
- Short Circuit Protection
- DC Output Voltage Protection
- Load Protection
- Switching Power Supply

TECHNICAL SPECIFICATION

SPECIFICATIONS

Number of Amplifier Channels	2
Peak Total Output	2,750W
Peak Output Voltage Per Channels	90Vrms
Max Output Power Per Channels	4Ω 1,400W / 8Ω 800W
Max Output Power Bridged	8Ω 2,750W

PERFORMANCE

Frequency Response	20Hz - 20kHz
THD+N(1kHz, @4Ω, -10dB)	<0.03%
Signal to Noise Ratio	>105dB
Damping Factor(10-400Hz,8Ω)	>300

GAIN, SENSITIVITY

Sensitivity Selectable All Channel	0.775V, 14V, 32dB
------------------------------------	-------------------

CONNECTORS AND BUTTONS

Input Connectors	3-Pin XLR
Output Connectors	4-Pin SpeakOn / Binding Posts 2-Pole
Output Bridge Mode	A+B (CH A is Input Source)
Mode	Mono, Stereo, Bridge
Intelligent Fans	Depending on Presence of Output Signal
Cooling	Dual Fan, Front to Rear Airflow

POWER

Operating Voltage, 220V	170-264V
Mains Connector	230V IEC: Standard

SIZE

Height	88mm(2U)
Width	483mm
Depth	416mm
Weight	10.5kg

