

VEDA SERIES II

VD-12M TWO-WAY STAGE MONITOR SPEAKER

DESCRIPTIONS

The Veda Series II : VD-12M from VL Audio is a passive stage monitor designed to deliver a highly versatile solution, from fixed installations to the popular portable PA applications. Its rotatable horn with 90° x 60° dispersion means the enclosure can also be used as a PA system.

FEATURE

- 98dB Sensitivity, 134dB maximum SPL
- System rating : 400W Continuous, 1600W Peak
- Designed to work with Veda Series II system



TECHNICAL SPECIFICATION

SPECIFICATIONS

Frequency Response(-3dB)	58Hz - 16kHz
Frequency Range(-6dB)	48Hz - 18.5kHz
Max. Calculated SPL	134dB
Nominal Directivity	90°H x 60°V
Crossover Point	1.5kHz

TRANSDUCER

LF Transducer	12" Transducer, 3" Voice Coil (12FW76)
LF Sensitivity @1w/1m	98dB
LF Nominal Impedance	8Ω
LF Power Handling	400W(Continuous), 1600(Peak)
HF Transducer	1.7" (ND44)
HF Sensitivity @1w/1m	106dB
HF Nominal Impedance	8Ω
HF Power Handling	100W(Continuous), 400(Peak)

INPUT/OUTPUT SECTION

Input Connector	V-Connect VC-S4FM(1+,1-)
Output Connector	V-Connect VC-S4FM(1+,1-)

PHYSICAL SPECIFICATIONS

Cabinet/Case Material	15mm Plywood with water based textured coatings
Handles	2 Handle
Pole Mount/Cap	Yes
Grille	Steel 1.4mm
Color	Black

SIZE

Height	370mm
Width	475mm
Depth	588mm
Weight	30kg

